



ACRYLICON  
IRELAND



## CONTACT US

Aoibheann - +353 87 362 9896

[Aoibheann.Haladek@acrylicon.ie](mailto:Aoibheann.Haladek@acrylicon.ie)

OR

Contact the office

Email - [info@Acrylicon.ie](mailto:info@Acrylicon.ie)

Call - +353 45 982 632

## ACRYLICON FLAKE SYSTEM

### TAILORED FOR YOUR INDUSTRY

The Acrylicon Flake System is 2-3mm thick and encapsulates decorative flakes within its chemically bonded monolithic structure. The system is designed for heavy traffic and moderate industrial use, combining unparalleled longevity with great aesthetics and is available in a multitude of colours. By using our exclusive blend of colour flakes, we are able to provide granite or marble style floors in a fraction of the time normally associated with the traditional systems.



## PREMIUM FLOORING

SOME RECENTLY COMPLETED PROJECTS INCLUDE WOOFIES KENNELS IN STRAFFAN, WICKLOW ANIMAL WELFARE AND CLONMEL VETINARY HOSPITAL. WHY NOT BE NEXT?

[www.Acrylicon.ie](http://www.Acrylicon.ie)





## KEY FEATURES & BENEFITS

Decorative finish - great aesthetics, UV stable and available in a wide range of colours.

Non Toxic Non Taintable - ideal for any premises catering to all domesticated and wild fauna that need pet friendly flooring.

Slip resistant - our floors exceed minimum safety requirements and can be tailored to each area.

High compressive strength - excellent durability and cleanability.

Chemical bond/cure - a truly seamless floor with no cold joints and virtually no risk of delamination.

Low emissions - our products are solvent-free and contain very low VOC's.

Long lasting - our floors do not degrade or become brittle with use.



## Unique Features of our floor

- 1. Sanitation:** Acrylicon floors are seamless and non-porous. This is critical in the veterinary industry for infection control. Acrylicon floors are chemically resistant to urine and animal waste and do not allow water, bodily fluids or any other liquid contaminants to seep into the floor structure.
- 2. Anti-Slip:** The highest level of anti-slip to meet new HSA Health and Safety requirement.
- 3. Easy to Clean:** The unique 94 newton surface strength is twice as tough as similar floor types, meaning the dirt stays on the surface and is much easier to clean compared with other floors. Simply clean down and wet vac to have a clean, hygienic floor each day.
- 4. Cure Time:** 2 hours which means you can work on the floor 2 hours after its installation.
- 5. A 10 Year Warranty:** We are happy to offer a 10 year warranty with our installations and have references floor in excess of 38 years still meeting requirements.

# FLOORING SPECIFICATIONS

Product - Acrylicon Flake System - Preparatory work and application in accordance with supplier's instructions.

Finish and Thickness - Satin 2-3mm finish

Slip Resistance - For added slip resistance our Flake Plus option is available in different grades.

Colour - wide range of options are available, consult the with our team for colour mix variations

Supplier - Acrylicon Polymers GmbH (Germany)

